



[ABOUT US](#) [PRODUCTS](#)

### STANDARD FEATURES

- Drivable at full height
- Variable speed, front wheel hydraulic drive
- DC Motor controller
- Half height hinged gate
- Dual holding brakes
- Proportional controls for drive & lift functions
- 3' (0.9 m) Roll out extension deck
- 24V DC power source
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires
- Pothole protection system
- 110V AC outlet on platform with GFI
- 28 mph wind rating (12.5m/sec)
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Hinged railing system
- Forklift pockets and tie down/lift lugs
- Relay based control system
- Color coded and numbered wiring system
- Telematics ready

(Preliminary specs)

### OVERALL SPECIFICATIONS

Work Height	45.5' (13.8 m)
Raised Platform Height	39.5' (12.0 m)
Lowered Platform Height	54" (1.37 m)
Overall Width	47" (1.19 m)
Overall Length	94.5" (2.40 m)
Stowed Height (Rails Up)	97.9" (2.49 m)
Stowed Height (Rails Down)	78.2" (1.99 m)
Platform Width (Inside Dimension)	42" (1.06 m)
Platform Length (Inside Dimension)	86" (2.19 m)
Extension Deck (Roll Out)	3' (0.9 m)
Ground Clearance (raised)	3.19" (8.1 cm)
Wheelbase	73" (1.85 m)
Weight	7480 lbs (3393 kg)
Gradeability	25%
Turning Radius (Inside)	21" (0.54 m)
Turning Radius (Outside)	101" (2.58 m)
Lift Time (With Rated Load)	71 sec
Lower Time (With Rated Load)	41 sec
Drive Speed (Stowed)	2.0 mph (3.2 km/h)
Drive Speed (Raised)	0.62 mph (1.0 km/h)
Maximum Drive Height	Full Height
Capacity (Overall)	500 lbs (227 kg)
Maximum # of Persons	2
Wind Rating	28 mph (12.5 m/s)
Tire Type	Solid, N/M
Tire Size	16 x 5 x 12